

Rittal – The System.

Faster – better – everywhere.



Colocation Rack Information Card

Rittal Colo Cabinet Options

47u 6x12 with divider & baying kit

47u 8x12 with divider & baying kit

Dimensions (mm) & package weight

600(w) 1200(d) 2200(h) ~125kg

800(w) 1200(d) 2200(h) ~130kg

- Welded steel frame
- Meshed front door (78% open area)
- Divided meshed rear doors (78% open area)
- 500mm twin brush cable entry top cover
- 4-digit combination handles with override key (F&R)
- 19" adjustable angles, front & rear (1500 kg)
- Front angles 88mm, 745mm gap to rear angles
- Air baffle fitted to front angles
- 800mm includes 6x 1u vertical mountings
- 158mm cable tray (fitted rear right)
- Earth bonding kit, fixing stud base of frame left side
- Slide-in divider/partition panel (fitted left side)
- User manual and keys
- Baying kit, pk4 (supplied with O&M pack)
- 10x caged nuts & screws (supplied with O&M pack)

Standard TS-IT end of row side panels available as required. Delivery costs TBC, depending on location & service.

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES



1-800-399-0748, IT@rittal.ca